



Seamark ZM Technology Group (H.K,) CO.,Ltd

Add: Building 10, Huaide Cuihai industrial Park, Fuyong Street, Bao'an district, Shenzhen, China

www.seamarkxray.com

Mobile:+8618779975930

Fax:0755-29929953

E-mail: info@seamarkxray.com

Seamark Xray X6600 advantages

1. The equipment complies with CE, FDA, China exemption certificate and other certificates
2. The size of the detectable platform area is 500 * 450mm (Support the maximum size of the sample is 640 * 540mm) , Load capacity \leq 10KG, the detector can be tilted 60 degrees, and the imaging is 2.5D
3. Closed tube optional 90kv / 100kv / 130kv / 150kv (standard 90 / 130kv), copper plate can penetrate 3mm, aluminum plate can penetrate 5.5mm
4. x ray tube is produced by Hamamatsu, the world's top closed tube manufacturer
5. The detector uses Korean Rayence HD CMOS flat panel detector with high fidelity
6. Safety protection, 5mm (90kv)- 5.5mm (130KV) isolated lead plate , safety lock, glass windows and other doors cannot be opened during normal operation of the machine
7. Software operation is convenient and fast, and the function is complete
8. Provide local installation and training
9. Can be networked, support data backup and traceability
10. X ray equipment with automatic CNC detection function, automatic detection to generate pictures
11. Configured by advantech's best brand industrial computer
12. Can automatically detect the bubble rate in the area
13. Convenient operation, the mouse can be operated without manual remote control + button
14. Simple and automatic BGA solder ball diameter and bubble ratio measurement
15. Support international power supply (AC110-220V)
16. Suitable for testing semiconductor, PCBA board, LED, electronic manufacturing bridges, voids, open circuits, more tin and less tin, broken wires and other quality defects
17. X ray tube maintenance-free, and has a long service life
18. Suitable for high-volume bubble detection

X6600 优点

1. 设备符合且有 CE, FDA, 中国豁免证书等证书
2. 可检测平台区域大小为 500*450mm, 探测器可倾斜 60 度(现在外称 45 度), 成像 2.5D
3. 闭管 Closed tube 可选 90kv/100kv/130kv/150kv (标配 90/130kv), 铜板可穿透 3mm, 铝板可穿透 5.5mm, 可免维护
4. 光管是世界顶级闭管厂家日本滨松生产的
5. 平板采用韩国高清 cmos 平板探测器, 高保真
6. 安全防护, 5mm 的隔离铅板, 安全锁, 在机器正常操作期间, 无法打开玻璃窗和其他的



Seamark ZM Technology Group (H.K.) CO.,Ltd

Add: Building 10, Huaide Cuihai industrial Park, Fuyong Street, Bao'an district, Shenzhen, China
www.seamarkxray.com

Mobile:+8618779975930

Fax:0755-29929953

E-mail: info@seamarkxray.com

门

7. 软件方便快捷， 功能齐全
8. 提供当地安装和培训
9. 可联网， 支持数据备份和可追溯

10. 设备带有自动 CNC 检测功能， 自动检测生成图片
11. 配置了 advantech 全球最好的品牌工控机
12. 可自动检测区域内的气泡率
13. 便捷的操作性， 鼠标即可实现操作， 无需繁琐的遥控+按钮
14. 简便 BGA 锡球直径和气泡比例自动量测生成检视报表
15. 可支持国际通用之供电方式（AC110-220V）

16. 适用于检测半导体、PCBA 板、LED、 电子制造和半导体桥接、 空洞、 开路、 多锡少锡、 断线等品质缺陷
17. 光管方便维护,使用寿命长
18. 适合大批量的气泡检测